What is claimed is:

1. A condensing gas boiler having a corrosion prevention structure of preventing corrosion caused by using heterogeneous metal, the condensing gas boiler comprising:

a casing provided with a combustion chamber therein;

a present heat exchanger arranged in the casing, which includes a first tubular tube made of a copper material having a plurality first thermal pins formed by processing an outer circumferential surface;

a latent heat exchanger disposed at a distance from the present heat exchanger, which includes a second tubular tube whose inner portion is made of a copper material and whose outer portion is made of aluminum, having a plurality second thermal pins formed by processing an outer circumferential surface;

end plates contacting and engaged with each other while the present heat exchanger and the latent heat exchanger are fixedly arranged in respective rows and installed in the casing; and

a plurality of connection tubes which are mutually connected through a connection portion so that water can circulate through the present heat exchanger and the latent heat exchanger,

wherein connection tubes which are made of a corrosion-resistant material are installed to have a broader area, and simultaneously connection tubes which are made of a corrosion-easy material are installed to have a smaller area, to thereby suppress galvanic corrosion through an unfavorable area ratio, and

wherein an insulator for electrical insulation is provided between the end plates.

2. The condensing gas boiler of claim 1, wherein at least a part of the connection portion is insulated.

3. The condensing gas boiler of claim 1, wherein an insulation packing is

interposed between the connection portion and the latent heat exchanger, in order to insulate the contacting surface between the connection portion and the latent heat exchanger.

4. The condensing gas boiler of claim 1, wherein the insulator provided between the end plates, is an insulation material interposed between the end plates to accomplish an insulation packing.

5. The condensing gas boiler of claim 1, wherein the contacting surface of the end plates is electrically insulated and coated, as the insulator provided between the end plates.